NSN 5305-00-042-4209

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-042-4209

view Offiline at https://aerobasegroup.com/histi/3303-00-042-4203
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.733 inches and 0.844 inches
Fastener Length:
Between 0.844 inches and 0.875 inches
Head Style:
Hexagon
Head Height:
Between 0.208 inches and 0.230 inches
Width Between Flats:
Between 0.489 inches and 0.500 inches
Washer Quantity:
1
Internal Drive Style:
Slot
Thread Diameter:
0.312 inches
Thready Qty Per Inch (tpi):
18
Hardness Rating:
40.0 rockwell c primary washer and 50.0 rockwell c primary washer
Primary Washer Outside Diameter:
Between 0.567 inches and 0.590 inches
Primary Washer Style:
Flat external teeth
Primary Washer Material Thickness:
Between 0.028 inches and 0.034 inches
Special Features:
W/header point
Material:
Steel comp 1020 or steel comp 1050
Material Specification:
Sae assn standard all material responses
Surface Treatment:
Cadmium or zinc
Surface Treatment Specification:
Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response
Thread Series Designator:

Unc

NSN 5305-00-042-4209

Assembled Washer Screw - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0