

View Online at <https://aerobasegroup.com/nsn/5305-00-042-4215>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.719 inches and 0.844 inches

Fastener Length:

Between 0.844 inches and 0.875 inches

Head Style:

Hexagon

Head Height:

Between 0.270 inches and 0.295 inches

Width Between Flats:

Between 0.551 inches and 0.562 inches

Washer Quantity:

1

Internal Drive Style:

Slot

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

16

Hardness Rating:

40.0 rockwell c primary washer and 50.0 rockwell c primary washer

Primary Washer Outside Diameter:

Between 0.640 inches and 0.660 inches

Primary Washer Style:

Flat external teeth

Primary Washer Material Thickness:

Between 0.032 inches and 0.040 inches

Special Features:

W/header point

Material:

Steel comp 1020 or steel comp 1050

Material Specification:

Sae assn standard all material responses

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0