Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-042-4218



Thread Class: 2a Thread Direction: Right-hand Thread Length: Between 1.313 inches and 1.438 inches Fastener Length: Between 1.438 inches and 1.500 inches Head Style: Hexagon Head Height: Between 0.270 inches and 0.295 inches Width Between Flats: Between 0.551 inches and 0.562 inches Washer Quantity:

1

Internal Drive Style:

Slot

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

16

Hardness Rating:

40.0 rockwell c primary washer and 50.0 rockwell c primary washer

Primary Washer Outside Diameter:

Between 0.640 inches and 0.660 inches

Primary Washer Style:

Flat external teeth

Primary Washer Material Thickness:

Between 0.032 inches and 0.040 inches

Special Features:

W/header point

Material:

Steel comp 1020 or steel comp 1050

Material Specification:

Sae assn standard all material responses

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response

Thread Series Designator:

Unc

NSN 5305-00-042-4218

Assembled Washer Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

