## NSN 5305-00-042-4507

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-042-4507 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.625 inches **Fastener Length:** 0.625 inches **Head Style:** Round **Head Diameter:** Between 0.334 inches and 0.359 inches **Head Height:** Between 0.123 inches and 0.137 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 40.0 rockwell c primary washer and 50.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.372 inches and 0.383 inches **Primary Washer Style:** Flat internal teeth **Primary Washer Material Thickness:** 0.022 inches Material: Steel or steel comp 1010 or steel comp 1050 or steel comp 1566 **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unf Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5305-00-042-4507

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0