Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-042-4509

| Thread Class:  |
|--|
| 2a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.875 inches   |
| Fastener Length:   |
| 0.875 inches   |
| Head Style:  |
| Round  |
| Head Diameter:   |
| Between 0.334 inches and 0.359 inches  |
| Head Height:   |
| Between 0.123 inches and 0.137 inches  |
| Washer Quantity:   |
| 1  |
| Internal Drive Style:  |
| Cross recess type 1  |
| Thread Diameter:   |
| 0.190 inches   |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Hardness Rating:   |
| 40.0 rockwell c primary washer and 50.0 rockwell c primary washer  |
| Primary Washer Outside Diameter:   |
| Between 0.372 inches and 0.383 inches  |
| Primary Washer Style:  |
| Flat internal teeth  |
| Primary Washer Material Thickness:   |
| 0.022 inches   |
| Material:  |
| Steel or steel comp 1010 or steel comp 1050 or steel comp 1566   |
| Material Specification:  |
| Sae assn standard all material responses   |
| Surface Treatment:   |
| Cadmium or zinc  |
| Surface Treatment Specification:   |
| Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response |
| Thread Series Designator:  |
| Unf<br>Shalf Life:   |
| Shelf Life:  |
| N/a  |

## NSN 5305-00-042-4509

Assembled Washer Screw - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0