Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-042-5589



Thread Class: 2a **Thread Direction: Right-hand Thread Length:** Between 0.511 inches and 0.594 inches Fastener Length: Between 0.594 inches and 0.625 inches **Head Style:** Hexagon **Head Height:** Between 0.208 inches and 0.230 inches Width Between Flats: Between 0.491 inches and 0.500 inches Washer Quantity: 1 **Internal Drive Style:** Slot **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 40.0 rockwell c and 50.0 rockwell c Primary Washer Outside Diameter: Between 0.567 inches and 0.590 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.028 inches and 0.034 inches Material: Steel comp 1010 or steel comp 1020 or steel comp 1050 **Surface Treatment:** Cadmium or zinc Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unf Shelf Life: N/a

- Unit Of Measure:
- ---

NSN 5305-00-042-5589

Assembled Washer Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

