Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-042-5598



Thread Class: 2a **Thread Direction: Right-hand Thread Length:** Between 0.511 inches and 0.594 inches Fastener Length: Between 0.594 inches and 0.625 inches **Head Style:** Hexagon **Head Height:** Between 0.270 inches and 0.295 inches Width Between Flats: Between 0.552 inches and 0.562 inches Washer Quantity: 1 **Internal Drive Style:** Slot **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): **Primary Washer Style:** Shelf Life:

24

Primary Washer Outside Diameter:

Between 0.640 inches and 0.660 inches

Flat external teeth

Primary Washer Material Thickness:

Between 0.032 inches and 0.040 inches

Material:

Steel comp 1010 or steel comp 1020 or steel comp 1050

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response

Thread Series Designator:

Unf

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5305-00-042-5598

Assembled Washer Screw - Page 2 of 2

Fiig: A003b0

