
Assembled Washer Screw - Page 1 of 2





## **Thread Class:** 2a **Thread Direction: Right-hand Thread Length:** Between 0.761 inches and 0.844 inches Fastener Length: Between 0.844 inches and 0.875 inches Head Style: Hexagon **Head Height:** Between 0.270 inches and 0.295 inches Width Between Flats: Between 0.552 inches and 0.562 inches Washer Quantity: 1 **Internal Drive Style:** Slot **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 **Primary Washer Outside Diameter:** Between 0.640 inches and 0.660 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.032 inches and 0.040 inches Material: Steel comp 1010 or steel comp 5135h or steel comp 1050 **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure: ---**Demilitarization:**

No

## NSN 5305-00-042-5600

Assembled Washer Screw - Page 2 of 2

**Fiig:** A003b0

