NSN 5305-00-042-8995

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-042-8995
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.875 inches
Fastener Length:
1.250 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.429 inches and 0.438 inches
Head Height:
Between 0.306 inches and 0.312 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.312 inches
Width Across Flats:
Between 0.218 inches and 0.220 inches
Thready Qty Per Inch (tpi):
24
Hardness Rating:
35.0 rockwell c and 43.0 rockwell c
Minimum Yield Strength:
140000 pounds per square inch
Material:
Steel comp 2340 or steel comp 3135 or steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 4340 or steel comp 8630
or steel comp 8740 or steel
Material Specification:
Qq-s-624 federal specification 1st material response or qq-s-624 federal specification 2nd material response or qq-s-624 federal
specification 3rd material response or qq-s-624 federal specification 4th material response or qq-s-624 federal specification 5th material
response or qq-s-624 federal specification 6th material response or qq-s-624 federal specification 7th material response or qq-s-624
federal specification 8th material response or qq-s-624, fs9440 federal specification 9th material response
Surface Treatment:
Cadmium or zinc
Thread Series Designator:
Unf
Specification Or Standard:
1 type and 11 style
Shelf Life:
N/a
Unit Of Measure:

Domilitarization

NSN 5305-00-042-8995

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0