NSN 5305-00-043-0506

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-043-0506 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 0.875 inches **Head Style:** Fillister **Head Diameter:** Between 0.250 inches and 0.270 inches **Head Height:** Between 0.106 inches and 0.113 inches **Hole Diameter:** 0.046 inches First Diameter From Head: Between 0.120 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.625 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches **Hole Quantity:** 1 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 60000 pounds per square inch **Hole Configuration Style:** Round **Externally Relieved Body Diameter Quantity:** Material: Steel comp 1010 **Material Specification:** Qq-s-630 federal specification single material response or qq-s-631 federal specification single material response or qq-s-634 federal

Surface Treatment:

Cadmium and chromate

specification single material response

NSN 5305-00-043-0506

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0