

View Online at <https://aerobasegroup.com/nsn/5305-00-043-0539>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.268 inches and 0.315 inches

**Fastener Length:**

2.582 inches

**Head Style:**

Crowned hexagon

**Head Height:**

Between 0.131 inches and 0.141 inches

**Width Between Flats:**

Between 0.429 inches and 0.439 inches

**Grip Diameter:**

Between 0.2483 inches and 0.2492 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 2.125 inches and 2.145 inches

**Thready Qty Per Inch (tpi):**

28

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.464 inches first hole

**Special Features:**

Retaining elements in shank matt2aadsta000

**Material:**

Steel

**Material Specification:**

1886 fscm 88277 mfr ref single material response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0