

View Online at <https://aerobasegroup.com/nsn/5305-00-044-3507>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.500 inches

Fastener Length:

0.500 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.473 inches and 0.492 inches

Head Height:

Between 0.130 inches and 0.144 inches

Internal Drive Style:

Slot

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

20

Screw Material:

Steel or steel comp 1006 or steel comp 1008 or steel comp 1010 or steel or steel comp 1025 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1038 or steel comp 1040 or steel comp 1045

Screw Material Specification:

Qq-s-633-canc federal specification 1st material response or qq-w-409, grade 2 federal specification 2nd material response or qq-w-409, grade 2 federal specification 3rd material response or qq-w-409, grade 2 federal specification 4th material response or qq-w-409, grade 2 federal specification 5th material response or qq-w-409, grade 3 federal specification 6th material response or qq-w-409, grade 4 federal specification 7th material response or qq-w-409, grade 4 federal specification 8th material response or qq-w-409, grade 4 federal specification 9th material response or qq-w-409, grade 4 federal specification 10th material response or qq-w-409, grade 4 federal specification 11th material response or qq-w-409, grade 4 federal specification 12th material response or qq-w-409, grade 4 federal specification 13th material response or qq-w-409, grade 4 federal specification 14th material response

Screw Surface Treatment:

Cadmium and chromate or zinc and chromate

Thread Series Designator:

Unc

Specification Or Standard:

1 type and 9s style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0