## NSN 5305-00-045-4834

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-045-4834 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.234 inches and 0.266 inches **Fastener Length:** Between 0.984 inches and 1.016 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.484 inches and 0.516 inches **Head Height:** Between 0.297 inches and 0.328 inches **First Diameter From Head:** Between 0.172 inches and 0.203 inches **Second Diameter From Head:** Between 0.109 inches and 0.141 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.047 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.734 inches and 0.766 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 **Product Name:** Navy special project Material: Steel comp 303 **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment:** Oxide

**Surface Treatment Specification:** 

A296ma112 fscm 49956 mfr ref single treatment response

**Thread Series Designator:** 

Unf

## NSN 5305-00-045-4834

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0