

View Online at <https://aerobasegroup.com/nsn/5305-00-045-4834>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.234 inches and 0.266 inches

**Fastener Length:**

Between 0.984 inches and 1.016 inches

**Head Style:**

Knurled no. 1

**Head Diameter:**

Between 0.484 inches and 0.516 inches

**Head Height:**

Between 0.297 inches and 0.328 inches

**First Diameter From Head:**

Between 0.172 inches and 0.203 inches

**Second Diameter From Head:**

Between 0.109 inches and 0.141 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.047 inches and 0.078 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 0.734 inches and 0.766 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

2

**Product Name:**

Navy special project

**Material:**

Steel comp 303

**Material Specification:**

Qq-s-763 federal specification single material response

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

A296ma112 fscm 49956 mfr ref single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0