NSN 5305-00-050-9230

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-050-9230 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.542 inches and 0.625 inches **Fastener Length:** 0.625 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Cross recess type 1 **End Application:** Mrap rg-33 auv **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Screw Material Specification:** 66 federal standard all material responses **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 3 type and 9c style Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-050-9230 Machine Screw - Page 2 of 2



Fiig:

A500d0