Externally Relieved Body Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-051-2741

Thread Class: 2a Thread Length: Right-hand Thread Length: Between 0.490 inches and 0.270 inches Fastener Length: Between 0.490 inches and 0.520 inches Head Syle: Flat chamfer Head Diameter: Between 0.306 inches and 0.322 inches Head Height: Between 0.306 inches and 0.322 inches Head Height: Between 0.106 inches and 0.115 inches First Diameter From Head: Between 0.106 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.250 inches and 0.290 inches Head Diameter: Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.250 inches and 0.290 inches Internal Drive Style: Cross roces type 1 Thread Diameter: 0.164 inches Thread Qu Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Surface Treatment: Passivate and paint Thread Series Designator: Unc Surface Treatment: Passivate and paint Thread Series Designator: Unc Sheft Life: Na Ma Distance: Passivate and paint Thread Series Designator: Unc Between: Passivate and paint Thread Series Designator: Unc Between: Passivate and paint Thread Series Designator: Unc Passivate and paint Thread Series Designator: Passivate Passivate	
Thread Direction: Right-hand Thread Length: Between 0.190 inches and 0.270 inches Fastener Length: Between 0.480 inches and 0.520 inches. Head Style: Flat chamfer Head Dimeter: Between 0.306 inches and 0.322 inches Head Neight: Between 0.306 inches and 0.322 inches Head Neight: Between 0.105 inches and 0.115 inches First Diameter From Head: Between 0.200 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Destween 0.250 inches and 0.290 inches Intread Diameter: 0.164 inches Thread Diameter: 0.164 inches Thread Submeter: 0.164 inches Thread Diameter: 0.164 inches Starles stel S	Thread Class:
Right-hand Thread Length: Between 0.190 inches and 0.270 inches Fastener Length: Between 0.480 inches and 0.520 inches Head Siyle: Filst chamfer Head Diameter: Between 0.306 inches and 0.322 inches Head Height: Between 0.105 inches and 0.115 inches First Diameter From Head: Between 0.120 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.250 inches and 0.290 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Oty Per Inch (pt)): 32 Externally Releved Body Diameter Quantity: 1 Stainless steel Surface Treatment: Passivate and paint Thread Series Designator: Unc Sheft Life: Na Dirdic Measure: Image: Stainless teel Dirdic Treat Diameter: Dirdic Treat Diameter: Na Dirdic Treat Dingtator:	
Tread Length: Between 0.190 inches and 0.270 inches Fastener Length: Between 0.480 inches and 0.520 inches Head Style: Flat chamfer Head Diameter: Between 0.306 inches and 0.322 inches Head Diameter: Between 0.105 inches and 0.322 inches Head Diameter Between 0.105 inches and 0.115 inches First Diameter From Head: Between 0.200 inches and 0.290 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.250 inches and 0.290 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qt Per Inch (pi): 32 Externally Relieved Body Diameter Quantity: 1 Stainless steel Surface Treatment: Passivate and paint Thread Series Designator: Unc Sheff Life: Na Chof Measure: Image: Image: Between Data feed standard 595 no. 27038 and cone point Marcia: <tr< td=""><td></td></tr<>	
Between 0.190 inches and 0.220 inches Fastener Length: Between 0.480 inches and 0.520 inches Head Style: Flat chamfer Head Diameter: Between 0.306 inches and 0.322 inches Head Height: Between 0.105 inches and 0.115 inches First Diameter From Head: Between 0.120 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.250 inches and 0.290 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thread Style: Stainless steel Stainless steel Starface Treatment: Passivate and paint Thread Steise Designator: Inc Stainless steel Chried Treatment: Na Inc Stainless inglanate:	Right-hand
Fastener Length: Between 0.480 inches and 0.520 inches Head Style: Flat chamfer Head Diameter: Between 0.306 inches and 0.322 inches Head Height: Between 0.105 inches and 0.115 inches First Diameter From Head: Between 0.120 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.250 inches and 0.120 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thread Val Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Special Features: Color black federal standard 595 no. 27038 and cone point Material: Stainless stel Surface Treatment: Passivate and paint Thread Series Designator: Unc Sheft Irie: Na Unit Of Measure: Passivate and paint Thread Series Designator: Na Unit Of Measure:	Thread Length:
Between 0.480 inches and 0.520 inches Head Style: Flat chamfer Head Diameter: Between 0.306 inches and 0.322 inches Head Heigh: Between 0.105 inches and 0.115 inches First Diameter From Head: Between 0.120 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.250 inches and 0.290 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Oty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Special Features: Color black federal standard 595 no. 27038 and cone point Material: Stainless stel Surface Treatment: Passivate and paint Thread Series Designator: Unc Sheft Irie: Na Unit Of Measure: - Permilitarization: Na Dirie Na Dirie Sintines stel Stringen Seri	Between 0.190 inches and 0.270 inches
Head Style: Flat chamfer Head Diameter: Between 0.306 inches and 0.322 inches Head Heigh: Between 0.105 inches and 0.115 inches First Diameter From Head: Between 0.120 inches and 0.125 inches Diatcee From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.250 inches and 0.290 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thread Viewel Body Diameter Quantity: 1 Special Features: Color black federal standard 595 no. 27038 and cone point Material: Stainless steel Strines Steel Strine Steel Material: Passivate and paint Thread Series Designator: Unc Shef Life: Na Unt Of Measure: - Pamilitarization: No Fig:	Fastener Length:
Flat chamfer Head Diameter: Between 0.306 inches and 0.322 inches Head Heigh: Between 0.105 inches and 0.115 inches First Diameter From Head: Between 0.120 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.250 inches and 0.290 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thread Diameter: 0.164 inches Thread Qt Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Special Features: Color black federal standard 595 no. 27038 and cone point Material: Stainless steel Surface Treatment: Passivate and paint Thread Series Designator: Unc Sheff Life: Na Unit Of Measure: - Pamilitarization: No Fig:	Between 0.480 inches and 0.520 inches
Head Diameter: Between 0.306 inches and 0.322 inches Head Height: Between 0.105 inches and 0.115 inches First Diameter From Head: Between 0.120 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.250 inches and 0.290 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Stares Steel Stares Steel Stares Steel Stariness steel Surface Treatment: Passivate and paint Thread Series Designator: Unc Shelf Life: N/a Dit of Measure: - Penilitarization: No Fig:	Head Style:
Between 0.306 inches and 0.322 inches Head Height: Between 0.105 inches and 0.115 inches First Diameter From Head: Between 0.120 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.250 inches and 0.290 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Special Features: Color black federal standard 595 no. 27038 and cone point Material: Stainless steel Surface Treatment: Passivate and paint Thread Series Designator: Unc Shelf Life: N/a Unc Shelf Life: N/a Fig:	Flat chamfer
Head Height: Between 0.105 inchess and 0.115 inches First Diameter From Head: Between 0.120 inchess and 0.25 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.250 inches and 0.290 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Special Features: Color black federal standard 595 no. 27038 and cone point Material: Stainless steel Surface Treatment: Passivate and paint Thread Series Designator: Unc Shelf Life: Na Ditt Of Measure: ~ Demilitarization: No Fig:	Head Diameter:
Between 0.105 inches and 0.115 inches First Diameter From Head: Between 0.120 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.250 inches and 0.290 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Sternally Relieved Body Diameter Quantity: 1 Steinel Features: Color black federal standard 595 no. 27038 and cone point Material: Stainless steel Surface Treatment: Passivate and paint Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: - - Demilitarization: No Fig:	Between 0.306 inches and 0.322 inches
First Diameter From Head: Between 0.120 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.250 inches and 0.290 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Sternally Relieved Body Diameter Quantity: 1 Stein Features: Color black federal standard 595 no. 27038 and cone point Material: Stainless steel Surface Treatment: Passivate and paint Thread Series Designator: Unc Sheff Life: N/a Unit Of Measure: - Demilitarization: No	Head Height:
Between 0.120 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.250 inches and 0.290 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Special Features: Color black federal standard 595 no. 27038 and cone point Material: Stainless steel Surface Treatment: Passivate and paint Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Between 0.105 inches and 0.115 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:Between 0.250 inches and 0.290 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.164 inchesThready Qty Per Inch (tpi):32Externally Relieved Body Diameter Quantity:1Special Features:Color black federal standard 595 no. 27038 and cone pointMaterial:Stainless steelSurface Treatment:Passivate and paintThread Series Designator:UncSheff Life:N/aUnit Of Measure:-Panillitarization:NoFig:	First Diameter From Head:
Between 0.250 inches and 0.290 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Special Features: Color black federal standard 595 no. 27038 and cone point Material: Stainless steel Surface Treatment: Passivate and paint Thread Series Designator: Unc Shelf Life: N/a Dirt of Measure: - Pamilitarization: No Fig:	Between 0.120 inches and 0.125 inches
Internal Drive Style:Cross recess type 1Thread Diameter:0.164 inchesThready Qty Per Inch (tpi):32Externally Relieved Body Diameter Quantity:1Special Features:Color black federal standard 595 no. 27038 and cone pointMaterial:Stainless steelSurface Treatment:Passivate and paintThread Series Designator:UncShelf Life:N/aInit of Measure:Image:Formilitarization:NoFig:	Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Cross recess type 1 Thread Diameter: O.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Special Features: Color black federal standard 595 no. 27038 and cone point Material: Stainless steel Stainless steel Stainless steel Passivate and paint Thread Series Designator: Unc Shelf Life: N/a Inti Of Measure: Demiltarization: No Fig:	Between 0.250 inches and 0.290 inches
Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Special Features: Color black federal standard 595 no. 27038 and cone point Material: Color black federal standard 595 no. 27038 and cone point Material: Stainless steel Surface Treatment: Passivate and paint Thread Series Designator: Unc Shelf Life: N/a Dint Of Measure: Demilitarization: No Fig:	Internal Drive Style:
0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 1 Special Features: Color black federal standard 595 no. 27038 and cone point Material: Stainless steel Surface Treatment: Passivate and paint Thread Series Designator: Unc Shelf Life: N/a Unt Of Measure: Demilitarization: No Fig:	Cross recess type 1
Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Special Features: Color black federal standard 595 no. 27038 and cone point Material: Color black federal standard 595 no. 27038 and cone point Material: Stainless steel Sufface Treatment: Passivate and paint Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Thread Diameter:
32 Externally Relieved Body Diameter Quantity: 1 Special Features: Color black federal standard 595 no. 27038 and cone point Material: Stainless steel Stainless steel Surface Treatment: Passivate and paint Thread Series Designator: Unc Shelf Life: N/a Dint of Measure: Foenilitarization: No Fig:	0.164 inches
Externally Relieved Body Diameter Quantity: 1 Special Features: Color black federal standard 595 no. 27038 and cone point Material: Stainless steel Surface Treatment: Passivate and paint Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Thready Qty Per Inch (tpi):
1 Special Features: Color black federal standard 595 no. 27038 and cone point Material: Stainless steel Surface Treatment: Passivate and paint Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	32
Special Features: Color black federal standard 595 no. 27038 and cone point Material: Stainless steel Surface Treatment: Passivate and paint Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Externally Relieved Body Diameter Quantity:
Color black federal standard 595 no. 27038 and cone point Material: Stainless steel Surface Treatment: Passivate and paint Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1
Material:Stainless steelSurface Treatment:Passivate and paintThread Series Designator:UncShelf Life:N/aUnt Of Measure:Demilitarization:NoFig:	Special Features:
Stainless steel Surface Treatment: Passivate and paint Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Fig:	Color black federal standard 595 no. 27038 and cone point
Surface Treatment: Passivate and paint Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Material:
Passivate and paint Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Stainless steel
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment:
Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Passivate and paint
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Unc
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A003b0	Fiig:
	A003b0