NSN 5305-00-051-6882



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-051-6882 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.253 inches **Fastener Length:** 0.375 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.238 inches and 0.279 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 62000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Aluminum alloy 2024 or aluminum alloy 2017 **Screw Material Specification:** Qq-a-200 federal specification 1st material response or qq-a-225 federal specification 1st material response or qq-a-225 federal specification 2nd material response **Screw Surface Treatment:** Anodize **Screw Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 2 type and 3c style Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig: A500d0

No

NSN 5305-00-051-6882

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.