## NSN 5305-00-052-2221

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-052-2221

| Thread Class:  |
|--|
| 2a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.875 inches and 1.000 inches                              |
| Fastener Length:   |
| 1.000 inches   |
| Head Style:  |
| Fillister  |
| Head Diameter:   |
| Between 0.590 inches and 0.622 inches                              |
| Head Height:   |
| Between 0.242 inches and 0.253 inches                              |
| Hole Diameter:   |
| 0.070 inches   |
| Internal Drive Style:  |
| Slot   |
| Thread Diameter:   |
| 0.375 inches   |
| Hole Quantity:   |
| 1  |
| Thready Qty Per Inch (tpi):  |
| 16   |
| Min. Tensile Strength (psi):                                       |
| 55000 pounds per square inch                                       |
| Screw Material:  |
| Steel  |
| Screw Material Specification:                                      |
| Qq-s-633 federal specification single material response            |
| Screw Surface Treatment:   |
| Cadmium and chromate   |
| Screw Surface Treatment Specification:                             |
| Qq-p-416 type 2 cl 3 federal specification all treatment responses |
| Head Hole Configuration Style:                                     |
| Round  |
| Thread Series Designator:  |
| Unc  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |

--

## NSN 5305-00-052-2221

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0