NSN 5305-00-052-2234

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-052-2234

3a         3a         Thread Direction:         Right-hand         Thread Length:         1.377 inches         Fastener Length:         1.500 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.872 inches and 0.937 inches         Internal Drive Style:         Hexagon         Thread Diameter:         0.500 inches         Width Across Flats:         0.313 inches         Thready Qty Per Inch (tpi):         13         Min. Tensile Strength (psi):         160000 pounds per square inch         Hardness Rating:         30.000 pounds per square inch         Hardness Rating:         130000 pounds per square inch         Minimum Yield Strength:         130000 pounds per square inch         Material:         Steel         Material Specification:         Cadmium and chromate         Surface Treatment:         Cadmium and chromate         Surface Treatment Specification         Qu-p-416, type 2, cl 3 federal specification single treatment response         Thread Series Designator:         Unc	Thread Class:
Thread Direction:         Right-hand         Thread Length:         1.377 inches         Fastener Length:         1.300 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.872 inches and 0.937 inches         Internal Drive Style:         Hexagon         Thread Diameter:         0.500 inches         Vidth Across Flats:         0.500 inches         Vidth Across Flats:         0.313 inches         Thready Qty Per Inch (tpi):         13         Min. Tensile Strength (psi):         160000 pounds per square inch         Hardness Rating:         30.000 pounds per square inch         Minimum Yield Strength:         130000 pounds per square inch         Material:         Steel         Material Specification:         64 federal standard single material response         Steriel         Material Specification:         64 federal standard single material response         Surface Treatment:         Cardmium and chromate         Surface Treatment Specification:         Qap-416, type 2, cl 3 federal specification single treatment response	
Right-handRight-handThread Length:1.377 inchesFastener Length:1.500 inchesHead Style:Flat countersunkHead Diameter:Between 0.872 inches and 0.937 inchesInternal Drive Style:HexagonThread Diameter:0.500 inchesWidth Across Flats:0.500 inchesWidth Across Flats:0.313 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:30.000 pounds per square inchHardness Rating:130000 pounds per square inchMinimum Yield Strength:130000 pounds per square inchMaterial:SteelMaterial:SteelMaterial Specification:66 federal standard single material responseSurface Treatment:Cardnium and chromateSurface Treatment Specification single treatment responseFuread Series Designator:UncShelf Life:N/a	
TheoThread Length:1.377 inchesFastener Length:1.500 inchesHead Style:Flat countersunkHead Diameter:Between 0.872 inches and 0.937 inchesInternal Drive Style:HexagonThread Diameter:0.500 inchesWidth Across Flats:0.500 inchesWidth Across Flats:0.313 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):16000 pounds per square inchHardness Rating:30.000 pounds per square inchHardness Rating:30000 pounds per square inchHardness Rating:30000 pounds per square inchHardness Rating:30000 pounds per square inchCountersink Angle:Between 80.0 degrees and 84.0 degreesMaterial:SteelMaterial:Gardium and chromateSurface Treatment Specification:Qu-p-416, type 2, cl 3 federal specification single treatment responseThread Series Designator:UncShelf Life:N/a	
1.377 inchesFastener Length:1.500 inchesHead Style:Flat countersunkHead Diameter:Between 0.872 inches and 0.937 inchesInternal Drive Style:HexagonThread Diameter:0.500 inchesWidth Across Flats:0.500 inchesWidth Across Flats:0.313 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:30000 pounds per square inchCountersink Angle:Between 80.0 degrees and 84.0 degreesMaterial:SteelMaterial:Gardium and chromateSurface Treatment Specification:Quep-416, type 2, cl 3 federal specification single treatment responseThread Series Designator:UncShelf Life:N/a	5
Faster Length:1.500 inchesHead Style:Flat countersunkHead Diameter:Between 0.872 inches and 0.937 inchesInternal Drive Style:HexagonThread Diameter:0.500 inchesWidth Across Flats:0.313 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:30.00 pounds per square inchHardness Rating:30000 pounds per square inchMinimum Yield Strength:130000 pounds per square inchCountersink Angle:Between 80.0 degrees and 84.0 degreesMaterial:SteelMaterial:Cadmium and chromateSurface Treatment Specification:(adp-416, type 2, cl 3 federal specification single treatment responseChread Series Designator:UncShelf Life:N/a	-
1.500 inchesHead Style:Flat countersunkHead Diameter:Between 0.872 inches and 0.937 inchesInternal Drive Style:HexagonThread Diameter:0.500 inchesWidth Across Flats:0.313 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 43.0 rockwell cMinimum Yield Strength:130000 pounds per square inchHaterial:Between 80.0 degrees and 84.0 degreesMaterial:SteelMaterial Specification:64 federal standard single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qu-p-416, type 2, cl 3 federal specification single treatment responseInread Series Designator:UncShelf Life:N/a	
Head Style:         Flat countersunk         Head Diameter:         Between 0.872 inches and 0.937 inches         Internal Drive Style:         Hexagon         Thread Diameter:         0.500 inches         Width Across Flats:         0.313 inches         Thready Qty Per Inch (tpi):         13         Min. Tensile Strength (psi):         160000 pounds per square inch         Hardness Rating:         36.0 rockwell c and 43.0 rockwell c         Minimum Yield Strength:         130000 pounds per square inch         Countersink Angle:         Between 80.0 degrees and 84.0 degrees         Material:         Steel         Material Specification:         66 federal standard single material response         Surface Treatment:         Cadmium and chromate         Surface Treatment Specification:         Qu-p-416, type 2, cl 3 federal specification single treatment response         Thread Series Designator:         Unc         Shelf Life:         N/a	-
Flat countersunkHead Diameter:Between 0.872 inches and 0.937 inchesInternal Drive Style:HexagonThread Diameter:0.500 inchesWidth Across Flats:0.313 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 43.0 rockwell cMinimum Yield Strength:130000 pounds per square inchMaterial:Between 80.0 degrees and 84.0 degreesMaterial Specification:6 federal standard single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qup-416, type 2, cl 3 federal specification single treatment responseInread Series Designator:UncShelf Life:Iv/a	
Head Diameter: Between 0.872 inches and 0.937 inches Internal Drive Style: Hexagon Thread Diameter: 0.500 inches Width Across Flats: 0.313 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Countersink Angle: Between 80.0 degrees and 84.0 degrees Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification single treatment response Thread Series Designator: Unc Shelf Life: N/a	-
Between 0.872 inches and 0.937 inches Internal Drive Style: Hexagon Thread Diameter: 0.500 inches Width Across Flats: 0.313 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Countersink Angle: Between 80.0 degrees and 84.0 degrees Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Cadmium and chromate Cadmium and chromate Thread Series Designator: Unc Shelf Life: N/a	
Internal Drive Style: Hexagon Thread Diameter: 0.500 inches Width Across Flats: 0.313 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Countersink Angle: Between 80.0 degrees and 84.0 degrees Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification single treatment response Thread Series Designator: Unc Shelf Life: N/a	
HexagonThread Diameter:0.500 inchesWidth Across Flats:0.313 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 43.0 rockwell cMinimum Yield Strength:130000 pounds per square inchCountersink Angle:Between 80.0 degrees and 84.0 degreesMaterial:SteelMaterial Specification:Cadmium and chromateSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qr.p-416, type 2, cl 3 federal specification single treatment responseLincShelf Life:N/a	
Thread Diameter:0.500 inchesWidth Across Flats:0.313 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:36.0 rockwell c and 43.0 rockwell cMinimum Yield Strength:130000 pounds per square inchCountersink Angle:Between 80.0 degrees and 84.0 degreesMaterial:SteelSteelMaterial Specification:64 federal standard single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qa-p-416, type 2, cl 3 federal specification single treatment responseUncShelf Life:N/a	
0.500 inches Width Across Flats: 0.313 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Countersink Angle: Between 80.0 degrees and 84.0 degrees Material: Steel Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a	-
Width Across Flats: 0.313 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Countersink Angle: Between 80.0 degrees and 84.0 degrees Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a	Thread Diameter:
0.313 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Countersink Angle: Between 80.0 degrees and 84.0 degrees Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a	0.500 inches
Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Countersink Angle: Between 80.0 degrees and 84.0 degrees Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a	Width Across Flats:
<ul> <li>13</li> <li>Min. Tensile Strength (psi):</li> <li>160000 pounds per square inch</li> <li>Hardness Rating:</li> <li>36.0 rockwell c and 43.0 rockwell c</li> <li>Minimum Yield Strength:</li> <li>130000 pounds per square inch</li> <li>Countersink Angle:</li> <li>Between 80.0 degrees and 84.0 degrees</li> <li>Material:</li> <li>Steel</li> <li>Material Specification:</li> <li>66 federal standard single material response</li> <li>Surface Treatment:</li> <li>Cadmium and chromate</li> <li>Surface Treatment Specification:</li> <li>Qq-p-416, type 2, cl 3 federal specification single treatment response</li> <li>Thread Series Designator:</li> <li>Unc</li> <li>Shelf Life:</li> <li>N/a</li> </ul>	0.313 inches
Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Countersink Angle: Between 80.0 degrees and 84.0 degrees Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a	Thready Qty Per Inch (tpi):
<ul> <li>160000 pounds per square inch</li> <li>Hardness Rating:</li> <li>36.0 rockwell c and 43.0 rockwell c</li> <li>Minimum Yield Strength:</li> <li>130000 pounds per square inch</li> <li>Countersink Angle:</li> <li>Between 80.0 degrees and 84.0 degrees</li> <li>Material:</li> <li>Steel</li> <li>Material Specification:</li> <li>66 federal standard single material response</li> <li>Surface Treatment:</li> <li>Cadmium and chromate</li> <li>Surface Treatment Specification:</li> <li>Qq-p-416, type 2, cl 3 federal specification single treatment response</li> <li>Thread Series Designator:</li> <li>Unc</li> <li>Shelf Life:</li> <li>N/a</li> </ul>	13
Hardness Rating:36.0 rockwell c and 43.0 rockwell cMinimum Yield Strength:130000 pounds per square inchCountersink Angle:Between 80.0 degrees and 84.0 degreesMaterial:SteelMaterial Specification:66 federal standard single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416, type 2, cl 3 federal specification single treatment responseThread Series Designator:UncShelf Life:N/a	Min. Tensile Strength (psi):
36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Countersink Angle: Between 80.0 degrees and 84.0 degrees Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a	160000 pounds per square inch
<ul> <li>Minimum Yield Strength:</li> <li>130000 pounds per square inch</li> <li>Countersink Angle:</li> <li>Between 80.0 degrees and 84.0 degrees</li> <li>Material:</li> <li>Steel</li> <li>Material Specification:</li> <li>66 federal standard single material response</li> <li>Surface Treatment:</li> <li>Cadmium and chromate</li> <li>Surface Treatment Specification:</li> <li>Qq-p-416, type 2, cl 3 federal specification single treatment response</li> <li>Thread Series Designator:</li> <li>Unc</li> <li>Shelf Life:</li> <li>N/a</li> </ul>	Hardness Rating:
130000 pounds per square inch Countersink Angle: Between 80.0 degrees and 84.0 degrees Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a	36.0 rockwell c and 43.0 rockwell c
Countersink Angle: Between 80.0 degrees and 84.0 degrees Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a	Minimum Yield Strength:
Between 80.0 degrees and 84.0 degrees Material: Steel Material Specification: 66 federal standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a	130000 pounds per square inch
Material:SteelMaterial Specification:66 federal standard single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416, type 2, cl 3 federal specification single treatment responseThread Series Designator:UncShelf Life:N/a	Countersink Angle:
Steel Material Specification: 66 federal standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a	Between 80.0 degrees and 84.0 degrees
Material Specification:66 federal standard single material responseSurface Treatment:Cadmium and chromateSurface Treatment Specification:Qq-p-416, type 2, cl 3 federal specification single treatment responseThread Series Designator:UncShelf Life:N/a	Material:
66 federal standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a	Steel
Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a	Material Specification:
Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a	66 federal standard single material response
Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a	Surface Treatment:
Qq-p-416, type 2, cl 3 federal specification single treatment response <b>Thread Series Designator:</b> Unc <b>Shelf Life:</b> N/a	Cadmium and chromate
Thread Series Designator: Unc Shelf Life: N/a	Surface Treatment Specification:
Unc Shelf Life: N/a	Qq-p-416, type 2, cl 3 federal specification single treatment response
Shelf Life: N/a	Thread Series Designator:
N/a	Unc
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:

## NSN 5305-00-052-2234

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

