NSN 5305-00-052-4032

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-052-4032

View Online at https://aerobasegroup.com/nsn/5305-00-052-4032
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.884 inches and 1.016 inches
Fastener Length:
Between 0.984 inches and 1.016 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.642 inches and 0.656 inches
Head Height:
Between 0.430 inches and 0.437 inches
Locking Feature:
Patch threads or pellet threads or strip threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.438 inches
Width Across Flats:
Between 0.375 inches and 0.379 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
170000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
150000 pounds per square inch
Material:
Steel
Material Specification:
66 federal standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Thread Series Designator:
Unjf
Specification Data:
80205-nas1351 professional/industrial association standard

80205-nas1351 professional/industrial association standard

NSN 5305-00-052-4032

Socket Head Cap Screw - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0