# NSN 5305-00-053-0615

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-053-0615



### Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

### **Thread Length:**

Between 0.325 inches and 0.375 inches

### Fastener Length:

0.375 inches

## Head Style:

Pan

## Head Diameter:

Between 0.205 inches and 0.219 inches

#### **Head Height:**

Between 0.070 inches and 0.080 inches

## **Internal Drive Style:**

Torque set

## Thread Diameter:

0.112 inches

## Thready Qty Per Inch (tpi):

40

## Min. Tensile Strength (psi):

140000 pounds per square inch

## Hardness Rating:

Between 248.0 brinell standard and 321.0 brinell standard

## **Screw Material:**

Iron alloy 660

## **Screw Material Specification:**

Ams 5732 assn standard single material response

## Screw Surface Treatment:

Passivate

## **Screw Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

## **Thread Series Designator:**

Unjc

#### Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A500d0

# NSN 5305-00-053-0615

Machine Screw - Page 2 of 2

## Mil-std (military Standard):

Mil-s-5002 spec.

