

View Online at <https://aerobasegroup.com/nsn/5305-00-053-1108>

Fastener Length:

Between 0.094 inches and 0.125 inches

Head Style:

Pan

Head Diameter:

Between 0.155 inches and 0.167 inches

Head Height:

Between 0.053 inches and 0.062 inches

Internal Drive Style:

Cross recess type 1

End Application:

W/s: aircraft, airlifter c-17a; aircraft (ac-130h, mc-130h, ec-130h, hc-130); helicopter, advance attack, ah-1w; engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); aircraft, c-2a (reprocured); engine, aircraft tf33-p-3/5/9 (c/ec-135, b-52h); sas (starting air sys), ffg-7; helicopter, mh-53e; engine, aircraft, tf-33-p-7 (c-141a/b)

Features Provided:

Casehardened

Nonmachine Thread Style:

Dog type (type b or c)

Nonmachine Thread Diameter:

0.086 inches

Material:

Steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1021 or steel comp 1022 or steel comp 1524

Material Specification:

Aisi assn standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification all treatment responses

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0