

View Online at <https://aerobasegroup.com/nsn/5305-00-053-1111>

Fastener Length:

Between 0.157 inches and 0.188 inches

Head Style:

Pan

Head Diameter:

Between 0.205 inches and 0.219 inches

Head Height:

Between 0.070 inches and 0.080 inches

Internal Drive Style:

Cross recess type 1

End Application:

W/s: engine, aircraft, f-108 (cfm-56, kc-135a); m1a2 abrams tank, 2350-01-328-5964 (eaa-cmbt85pk3); engine, aircraft, f100-pw-100 (f-15a/b/c/d); engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); aircraft, awacs, e-3a; engine, aircraft, tf39-ge-1 (c-5a); aircraft (ac130-h, mc-130h, ec-130e, hc-130); engine, aircraft, f100-pw-200 (f-16a/b/c/d); helicopter, mh-53e; engine, aircraft, tf-33-p-7 (c-141a/b)

Features Provided:

Casehardened

Nonmachine Thread Style:

Dog type (type b or c)

Nonmachine Thread Diameter:

0.112 inches

Material:

Steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1021 or steel comp 1022 or steel comp 1524

Material Specification:

Aisi assn standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification all treatment responses

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0