## NSN 5305-00-053-5729

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-053-5729 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.225 inches and 0.245 inches **Fastener Length:** Between 0.920 inches and 0.940 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.205 inches and 0.215 inches **Head Height:** Between 0.070 inches and 0.075 inches **First Diameter From Head:** 0.138 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.235 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 4130 or steel comp 4140 or steel comp 8740 **Material Specification:** Aisi 4130 assn standard 1st material response or aisi 4140 assn standard 2nd material response or aisi 8740 assn standard 3rd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 class 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5305-00-053-5729

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0