## NSN 5305-00-054-2031

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-054-2031 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.283 inches and 0.375 inches **Fastener Length:** Between 0.345 inches and 0.375 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Hole Diameter:** Between 0.044 inches and 0.050 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.156 inches and 0.159 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 15000 pounds per square inch **Hole Configuration Style:** Round internal hexagon Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** 

ourrace freatment opecinication

Ams-qq-p-416, type 2, cl 2 federal specification single treatment response

## NSN 5305-00-054-2031

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Departure From Cited Designator:
As mod by drilled holes through hd
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0