

View Online at <https://aerobasegroup.com/nsn/5305-00-054-4881>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.500 inches and 0.550 inches

**Fastener Length:**

Between 1.875 inches and 1.885 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.308 inches and 0.318 inches

**Head Height:**

Between 0.113 inches and 0.123 inches

**Internal Drive Style:**

Slot

**End Application:**

W/s: helicopter, seahawk, h-60; helicopter, cobra/tow, ah series; helicopter, super jolly h-53; helicopter, iroquois uh-1; helicopter, search and rescue, hh-60h; helicopter, carrier based asw, sh-60f; helicopter, hh-53h pave low; helicopter, uscg search and rescue, hh-60j; helicopter, uh-60a/uh-60d; helicopter, sea king h-3

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Screw Material:**

Steel

**Screw Surface Treatment:**

Cadmium and chromate

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0