NSN 5305-00-054-4997

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-054-4997 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.209 inches **Fastener Length:** 0.375 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.333 inches and 0.385 inches **Internal Drive Style:** Cross recess type 1 **End Application:** W/s: howitzer, m102; helicopter, uh-60a/uh-60d; aircraft, hercules c-130; aircraft (ac-130h, mc-130h, ec-130e, hc-130) **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 55000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Copper alloy **Screw Material Specification:** Qq-b-613 federal specification single material response or qq-b-626 federal specification single material response or qq-w-321 federal specification single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, ty2 cl3 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 3 type or 3c style Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5305-00-054-4997 Machine Screw - Page 2 of 2



Fiig:

A500d0