

View Online at <https://aerobasegroup.com/nsn/5305-00-054-4997>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.209 inches

**Fastener Length:**

0.375 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.333 inches and 0.385 inches

**Internal Drive Style:**

Cross recess type 1

**End Application:**

W/s: howitzer, m102; helicopter, uh-60a/uh-60d; aircraft, hercules c-130; aircraft (ac-130h, mc-130h, ec-130e, hc-130)

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

55000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Screw Material:**

Copper alloy

**Screw Material Specification:**

Qq-b-613 federal specification single material response or qq-b-626 federal specification single material response or qq-w-321 federal specification single material response

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416, ty2 cl3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

3 type or 3c style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0