NSN 5305-00-054-5165



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-054-5165 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.300 inches **Fastener Length:** 0.730 inches **Head Style:** Flat chamfer **Head Diameter:** 0.440 inches **Head Height:** Between 0.055 inches and 0.060 inches **Shoulder Diameter:** 0.249 inches first shoulder and 0.250 inches first shoulder **Shoulder Length:** 0.425 inches first shoulder and 0.430 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.070 inches first hole and 0.074 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 175000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 0.625 inches first hole and 0.635 inches first hole **Shoulder Shape:** Round first shoulder Material: Steel **Surface Treatment: Passivate Thread Series Designator:** Unf Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-054-5165

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0