

View Online at <https://aerobasegroup.com/nsn/5305-00-054-5667>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.381 inches and 0.431 inches

Fastener Length:

Between 2.516 inches and 2.546 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.339 inches and 0.381 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Steel comp 4130

Screw Material Specification:

Mil-s-6758 military specification single material response

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416, ty2 cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas583 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6758 spec.