NSN 5305-00-054-5678

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-054-5678 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.291 inches and 0.341 inches **Fastener Length:** Between 0.863 inches and 0.893 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.362 inches and 0.395 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.552 inches and 0.572 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp 4130 **Material Specification:** Mil-s-6758, cond d4 military specification single material response **Surface Treatment:** Cadmium and chromate **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No **Fiig:**

A003b0

NSN 5305-00-054-5678

Close Tolerance Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.