## NSN 5305-00-054-5708

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-054-5708

Thread Class:	
3a Thread Direction:	
Right-hand	
Thread Length:	
Between 0.291 inches and 0.341 inches	
Fastener Length:	
Between 0.926 inches and 0.956 inches	
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.362 inches and 0.395 inches	
Grip Diameter:	
Between 0.2485 inches and 0.2495 inches	
Internal Drive Style:	
Offset cruciform (torque set)	
Thread Diameter:	
0.250 inches	
Grip Length:	
Between 0.615 inches and 0.635 inches	
Thready Qty Per Inch (tpi):	
28	
Min. Tensile Strength (psi):	
160000 pounds per square inch	
Countersink Angle:	
100.0 degrees	
Material:	
Steel comp 4130	
Material Specification:	
Mil-s-6758, cond d4 military specification single material response	nse
Surface Treatment:	
Cadmium and chromate	
Thread Series Designator:	
Unf	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

## NSN 5305-00-054-5708

Close Tolerance Screw - Page 2 of 2

## Mil-std (military Standard):

Mil-s-6758 spec.

