## NSN 5305-00-054-8449

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-054-8449 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.349 inches and 0.399 inches **Fastener Length:** Between 1.047 inches and 1.077 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.441 inches and 0.474 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.678 inches and 0.698 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** 100.0 degrees **Surface Finish:** 63.0 microinches grip **Product Name:** Navy special project Material: Steel comp 4130 **Material Specification:** Mil-s-6758, cond d4 military specification single material response **Surface Treatment:** Cadmium and chromate **Thread Series Designator:** Unf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-00-054-8449

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.