## NSN 5305-00-054-9245

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-054-9245 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.515 inches and 0.562 inches **Fastener Length:** Between 1.203 inches and 1.250 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.447 inches and 0.507 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 85000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 321 or steel comp 347 **Screw Material Specification:** Qq-s-763 federal specification all material responses or 66 federal standard all material responses **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A500d0