NSN 5305-00-055-5769

Machine Screw - Page 1 of 2

Thread Class:

2a



View Online at https://aerobasegroup.com/nsn/5305-00-055-5769

| Thread Direction: |
|---|
| Right-hand |
| Thread Length: |
| 0.250 inches |
| Fastener Length: |
| 0.250 inches |
| Head Style: |
| Fillister |
| Head Diameter: |
| Between 0.292 inches and 0.313 inches |
| Head Height: |
| Between 0.123 inches and 0.130 inches |
| Hole Diameter: |
| 0.046 inches |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.190 inches |
| Hole Quantity: |
| 1 |
| Three dry Oty, Day Inch (to:). |
| Thready Qty Per Inch (tpi): |
| 32 |
| |
| 32 |
| 32 Min. Tensile Strength (psi): |
| 32 Min. Tensile Strength (psi): 55000 pounds per square inch |
| 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: |
| 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel |
| 32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: |
| Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: Cadmium and chromate |
| Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Head Hole Configuration Style: |
| Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Head Hole Configuration Style: Round |
| Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Head Hole Configuration Style: Round Thread Series Designator: |
| Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Head Hole Configuration Style: Round Thread Series Designator: Unf |
| Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Head Hole Configuration Style: Round Thread Series Designator: Unf Specification Or Standard: |
| Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Head Hole Configuration Style: Round Thread Series Designator: Unf Specification Or Standard: 1 type or 5s style |
| Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Head Hole Configuration Style: Round Thread Series Designator: Unf Specification Or Standard: 1 type or 5s style Departure From Cited Designator: |
| Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Head Hole Configuration Style: Round Thread Series Designator: Unf Specification Or Standard: 1 type or 5s style Departure From Cited Designator: As modified by tensile strength |
| Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Head Hole Configuration Style: Round Thread Series Designator: Unf Specification Or Standard: 1 type or 5s style Departure From Cited Designator: As modified by tensile strength Shelf Life: |
| Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Head Hole Configuration Style: Round Thread Series Designator: Unf Specification Or Standard: 1 type or 5s style Departure From Cited Designator: As modified by tensile strength Shelf Life: N/a |

NSN 5305-00-055-5769

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0