NSN 5305-00-055-5769

Machine Screw - Page 1 of 2

Thread Class:

2a



View Online at https://aerobasegroup.com/nsn/5305-00-055-5769

Thread Direction:
Right-hand
Thread Length:
0.250 inches
Fastener Length:
0.250 inches
Head Style:
Fillister
Head Diameter:
Between 0.292 inches and 0.313 inches
Head Height:
Between 0.123 inches and 0.130 inches
Hole Diameter:
0.046 inches
Internal Drive Style:
Slot
Thread Diameter:
0.190 inches
Hole Quantity:
1
Three dry Oty, Day Inch (to:).
Thready Qty Per Inch (tpi):
32
32
32 Min. Tensile Strength (psi):
32 Min. Tensile Strength (psi): 55000 pounds per square inch
32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material:
32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel
32 Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment:
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: Cadmium and chromate
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Head Hole Configuration Style:
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Head Hole Configuration Style: Round
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Head Hole Configuration Style: Round Thread Series Designator:
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Head Hole Configuration Style: Round Thread Series Designator: Unf
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Head Hole Configuration Style: Round Thread Series Designator: Unf Specification Or Standard:
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Head Hole Configuration Style: Round Thread Series Designator: Unf Specification Or Standard: 1 type or 5s style
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Head Hole Configuration Style: Round Thread Series Designator: Unf Specification Or Standard: 1 type or 5s style Departure From Cited Designator:
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Head Hole Configuration Style: Round Thread Series Designator: Unf Specification Or Standard: 1 type or 5s style Departure From Cited Designator: As modified by tensile strength
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Head Hole Configuration Style: Round Thread Series Designator: Unf Specification Or Standard: 1 type or 5s style Departure From Cited Designator: As modified by tensile strength Shelf Life:
Min. Tensile Strength (psi): 55000 pounds per square inch Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Head Hole Configuration Style: Round Thread Series Designator: Unf Specification Or Standard: 1 type or 5s style Departure From Cited Designator: As modified by tensile strength Shelf Life: N/a

NSN 5305-00-055-5769

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0