NSN 5305-00-056-2498

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-056-2498 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.178 inches and 0.198 inches **Fastener Length:** Between 0.609 inches and 0.641 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.090 inches and 0.110 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.302 inches and 0.322 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity: Special Features:** Point 0.609 in. Min Ig 0.641 in. Maximum Ig, point chamfer angle 15 deg Material: Steel comp 302 **Material Specification:** Aisi assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-056-2498

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0