
Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-056-3382

| View Online at https://aerobasegroup.com/nsn/5305-00-056-3382 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 1.250 inches and 1.375 inches |
| Fastener Length: |
| 2.500 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.365 inches and 0.375 inches |
| Head Height: |
| Between 0.244 inches and 0.250 inches |
| Shank Unthreaded Hole Diameter: |
| 0.080 inches first hole and 0.085 inches first hole |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.250 inches |
| Width Across Flats: |
| Between 0.187 inches and 0.190 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Hardness Rating: |
| 36.0 rockwell c and 45.0 rockwell c |
| Minimum Yield Strength: |
| 130000 pounds per square inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 0.120 inches first hole |
| Material: |
| Steel |
| Material Specification: |
| 66, cond a federal standard single material response |
| Surface Treatment: |
| Cadmium and chromate |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5305-00-056-3382

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

