# NSN 5305-00-057-0488

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-057-0488



# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

Between 0.079 inches and 0.219 inches

#### Fastener Length:

Between 0.266 inches and 0.312 inches

#### **Head Style:**

Flat countersunk

#### Head Diameter:

Between 0.283 inches and 0.332 inches

#### Internal Drive Style:

Cross recess type 1

# Thread Diameter:

0.164 inches

# Thready Qty Per Inch (tpi):

32

# Min. Tensile Strength (psi):

125000 pounds per square inch

### Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### **Screw Material:**

Steel comp 8630 or steel comp 4037

#### Screw Material Specification:

Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response

#### Screw Surface Treatment:

Cadmium and chromate

# Screw Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

#### **Thread Series Designator:**

Unc

#### Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A500d0

# NSN 5305-00-057-0488

Machine Screw - Page 2 of 2

# Mil-std (military Standard):

Mil-s-6050 spec.

