

View Online at <https://aerobasegroup.com/nsn/5305-00-057-0507>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.844 inches and 0.875 inches

Fastener Length:

Between 0.844 inches and 0.875 inches

Head Style:

Pan

Head Diameter:

Between 0.155 inches and 0.167 inches

Head Height:

Between 0.053 inches and 0.062 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.086 inches

Thready Qty Per Inch (tpi):

64

Min. Tensile Strength (psi):

80000 pounds per square inch

Screw Material:

Steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347

Screw Material Specification:

66 federal standard all material responses

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Specification Or Standard:

3 type and 9c style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0