Hexagon Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-057-1158

| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.500 inches |
| Fastener Length: |
| 1.500 inches |
| Head Height: |
| Between 0.302 inches and 0.323 inches |
| Width Between Flats: |
| Between 0.736 inches and 0.750 inches |
| Hole Diameter: |
| 0.094 inches |
| Thread Diameter: |
| 0.500 inches |
| Hole Quantity: |
| 1 |
| Ноје Туре: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 150000 pounds per square inch |
| Hardness Rating: |
| 32.0 rockwell c and 38.0 rockwell c |
| Minimum Yield Strength: |
| 120000 pounds per square inch |
| Hole Configuration Style: |
| Hexagon flats |
| Material: |
| Steel |
| Material Specification: |
| Sae gr 8 assn standard single material response |
| Surface Treatment: |
| Phosphate |
| Surface Treatment Specification: |
| Mil-c-16232, type 2 military specification single treatment response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| |

NSN 5305-00-057-1158

Hexagon Head Cap Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-16232 spec.