NSN 5305-00-057-2504

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-057-2504



Thread Class: 3a Thread Direction: Right-hand Thread Length:

Between 0.289 inches and 0.453 inches

Fastener Length:

Between 0.594 inches and 0.656 inches

Head Style:

Round extended washer

Head Diameter:

Between 0.427 inches and 0.447 inches

Head Height:

Between 0.096 inches and 0.106 inches

Extended Washer Diameter:

Between 0.490 inches and 0.510 inches

Extended Washer Thickness:

Between 0.028 inches and 0.033 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

62000 pounds per square inch

Screw Material:

Aluminum alloy 2024

Screw Material Specification:

Qq-a-200/3 federal specification single material response or qq-a-225/6 federal specification single material response

Screw Surface Treatment:

Anodize

Screw Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5305-00-057-2504

Machine Screw - Page 2 of 2

Fiig: A500d0

Mil-std (military Standard):

Mil-a-8625 spec.

