NSN 5305-00-057-3663

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-057-3663

view Offilite at https://aerobasegroup.com/histi/3303-00-037-3003	
Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.609 inches and 0.766 inches	
Fastener Length:	
Between 0.734 inches and 0.766 inches	
Head Style:	
Flat chamfer	
Head Diameter:	
Between 0.550 inches and 0.562 inches	
Head Height:	
Between 0.368 inches and 0.375 inches	
Locking Feature:	
Patch threads or pellet threads or strip threads	
Internal Drive Style:	
Hexagon	
Thread Diameter:	
0.375 inches	
Width Across Flats:	
Between 0.312 inches and 0.316 inches	
Thready Qty Per Inch (tpi):	
16	
Min. Tensile Strength (psi):	
180000 pounds per square inch	
Hardness Rating:	
39.0 rockwell c fastener and 45.0 rockwell c fastener	
Minimum Yield Strength:	
155000 pounds per square inch	
Material:	
Steel fastener	
Surface Treatment:	
Cadmium fastener and chromate fastener	
Surface Treatment Specification:	
Qq-p-416, type 2 cl 3 federal specification single treatment response fastener	
Thread Series Designator:	
Unrc	
Specification Data:	
80205-nas1352 professional/industrial association standard	
Shelf Life:	
N/a	

N/a

NSN 5305-00-057-3663

Socket Head Cap Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0