## NSN 5305-00-057-5975

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-057-5975 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.104 inches and 0.144 inches **Fastener Length:** Between 0.225 inches and 0.250 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.318 inches and 0.336 inches **Head Height:** Between 0.075 inches and 0.080 inches **Shoulder Diameter:** 0.155 inches first shoulder and 0.165 inches first shoulder **Shoulder Length:** 0.106 inches first shoulder and 0.121 inches first shoulder **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Shoulder Shape:** Round first shoulder Material: Steel comp 303 **Material Specification:** Astm a582 cond a assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5305-00-057-5975

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.