## NSN 5305-00-058-2063

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-058-2063 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.194 inches and 0.250 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.091 inches and 0.096 inches **Head Height:** Between 0.057 inches and 0.060 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.060 inches Width Across Flats: Between 0.050 inches and 0.051 inches Thready Qty Per Inch (tpi): 80 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 6 type Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-00-058-2063

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0