## NSN 5305-00-058-4007

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-058-4007

## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.429 inches and 0.578 inches Fastener Length: Between 1.766 inches and 1.812 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.447 inches and 0.507 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 8630 or steel comp 4037 **Screw Material Specification:** Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure: **Demilitarization:** No

Fiig:

--

A500d0

## NSN 5305-00-058-4007

Machine Screw - Page 2 of 2

## Mil-std (military Standard):

Mil-s-6050 spec.

