

View Online at <https://aerobasegroup.com/nsn/5305-00-058-5025>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

4.000 inches

Fastener Length:

Between 3.906 inches and 4.000 inches

Head Style:

Square

Head Height:

Between 0.452 inches and 0.485 inches

Width Between Flats:

Between 0.606 inches and 0.625 inches

Point Style:

Cup

Internal Drive Style:

W/o internal drive

Thread Diameter:

0.625 inches

Thready Qty Per Inch (tpi):

11

Hardness Rating:

30.0 rockwell c and 37.0 rockwell c

Material:

Steel comp 1010 or steel comp 1011 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1212 or steel comp 1213 or steel comp 1137 or steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1541 or steel comp 1042 or steel comp 1043 or steel comp 1045 or steel comp 1139 or steel comp 1140 or steel comp 1141 or steel comp 1144 or steel comp 1145

Material Specification:

66 federal standard all material responses

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 class 3 federal specification all treatment responses

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig: