NSN 5305-00-058-5053

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-058-5053 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.667 inches and 0.750 inches **Fastener Length:** 0.750 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.685 inches and 0.762 inches **Internal Drive Style:** Cross recess type 1 **End Application:** W/s: support equipment, c-17a aircraft; aircraft, hawkeye e-2c; over the horizon back scanner (oth-b) program (an/fps-118); aircraft, awacs, e-3a **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Screw Material Specification:** 66 federal standard all material responses **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

Fiig: A500d0

No

Demilitarization: