

View Online at <https://aerobasegroup.com/nsn/5305-00-059-3666>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.688 inches and 1.750 inches

Fastener Length:

1.750 inches

Head Style:

Pan

Head Diameter:

Between 0.357 inches and 0.373 inches

Head Height:

Between 0.122 inches and 0.133 inches

Internal Drive Style:

Cross recess type 1

End Application:

W/s: communications terminal, satellite an/gsc-3 (v)1; test station, oq-290(v)msm; support equipment, b-1 aircraft; boilers, 1200 psi; aircraft (ac-130h, mc-130h, ec-130e, hc-130); main feed pumps; trainer, b-1b aircraft; support equipment, b-52 aircraft; I aircraft, awacs, e-3a; fire control system, mk-92 (fcs)

Thread Diameter:

0.190 inches

Thread Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

80000 pounds per square inch

Screw Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

Screw Material Specification:

66 federal standard all material responses

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0