

View Online at <https://aerobasegroup.com/nsn/5305-00-059-3667>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.938 inches and 2.000 inches

Fastener Length:

2.000 inches

Head Style:

Pan

Head Diameter:

Between 0.357 inches and 0.373 inches

Head Height:

Between 0.122 inches and 0.133 inches

Internal Drive Style:

Cross recess type 1

End Application:

W/s: aircraft (ac-130h, mc-130h, ec-130e, hc-130); stream (std. Tensioned replenishment at sea method); fire control system, mk 92 (fcs); support equipment, b-1 aircraft; repair facility, oa8991; communications terminal, satellite an/gsc-3 (v)1; missile, air-to-air, phoenix (aim-54); missile, air intercept, sidewinder (aim-9); ground mobile force satellite comm term (an/tsc-85a)

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

80000 pounds per square inch

Screw Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

Screw Material Specification:

66 federal standard all material responses

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0